

High-speed 10/100 Switching for Rackmount or Desktop Installations



With its advanced switching technology, the Linksys 24-Port 10/100 Switch will boost your network performance with much more than just full duplex data transfer and dedicated bandwidth. It features non-blocking, wire-speed switching that forwards packets as fast as your network can deliver them. Also included are Address Learning and Aging to prevent data transfer errors and Data Flow Control to help prevent packet collisions.

You have several installation options. The Switch's compact size fits onto your desktop, or use the wall mount slots to hang it somewhere out of the way. If your network equipment is in a rack, install it using the included rack mount brackets.

No matter how intensive your network demands, the Linksys 24-Port 10/100 Switch has speed, flexibility, and reliability that you can count on.

24 Autosensing,
10/100, full-duplex,
auto MDI/MDI-X ports

Runs at non-block-
ing, full wire speeds
up to 200Mbps

Address Learning
and Data Flow Con-
trol for transmission
reliability

Suitable for both
desktop or rack-
mount installations

24-Port 10/100 Switch

Product Data

24-Port 10/100 Switch

Features

- Ideal for Integrating Your 10BaseT and 100BaseTX Network Hardware
- 24 10/100 Ports Provide Dedicated Bandwidth in Half- or Full-Duplex Modes
- Switched 10/100 Ports Run at up to 200Mbps in Full-Duplex Mode
- Each Port Supports Auto MDI/MDI-X Cable Detection
- Compatible with All Major Network Operating Systems
- Advanced Store-and-Forward Packet Switching Optimizes Data Transfers
- Auto Partitioning Protects PCs from Downed Network Lines
- Signal Regeneration Ensures Data Transfer Integrity
- Free Technical Support—24 Hours a Day, 7 Days a Week, Toll-Free US Calls
- Limited Lifetime Warranty

Specifications

Model	SR224
Standards	IEEE 802.3, IEEE 802.3u
Ports	24 10/100 RJ-45
Cabling Type	Category 5 Ethernet or Better
LEDs	System, 1 through 24
Security Features	Security Lock Slot

Environmental

Dimensions (W x D x H)	279.4 mm x 44.5 mm x 240 mm (11.00" x 1.75" x 9.45")
Unit Weight	3.3 lbs. (1.5 kg)
Power Input	12.5 W Internal 100 V ~ 240 VAC
Certifications	FCC Class B, CE
Operating Temp.	0°C to 50°C (32°F to 122°F)
Storage Temp.	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	20% to 95%, Non-Condensing
Storage Humidity	5% to 90%, Non-Condensing

Linksys
A Division of Cisco Systems, Inc.
18582 Teller Avenue
Irvine, CA 92612 USA

E-mail: sales@linksys.com
support@linksys.com

Web: <http://www.linksys.com>

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

Package Contents

- One SR224 24-Port 10/100 Switch
- One AC Power Cord
- One User Guide
- One Registration Card

Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2003 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.