

HP 1410 Switch Series



Product overview

The HP 1410 Switch Series comprises unmanaged Gigabit Ethernet and Fast Ethernet switches, designed for small businesses looking for entry-level low-cost networking solutions that come with a lifetime warranty. The series consists of nine models with flexible mounting options to meet different network switching needs. All models have quality of service (QoS) support and IEEE 802.3x flow control features that provide outstanding data efficiency.

Simplified plug-and-play convenience is enabled by features such as auto-MDIX and auto-speed negotiation. HP has innovated and combined the latest advances in silicon technology to bring you some of the most power-efficient switches—1410-24G-R, 1410-16, and 1410-24 models are advanced IEEE 802.3az-compliant unmanaged Gigabit and Fast Ethernet switches. The switches come with built-in green features and a lifetime warranty, making the series the right choice for organizations seeking a networking solution that's both economical and reliable.

A summary of the highlights of the 1410 Switch Series:

- Unmanaged Gigabit Ethernet and Fast Ethernet switches
- Green features for low power consumption
- Fan-less design for silent operation
- QoS support
- Lifetime warranty

Features and benefits

QoS

- IEEE 802.1p prioritization
Delivers data to devices, based on the priority and type of traffic
- DiffServ Code Point (DSCP) support
Allows real-time traffic prioritization, based on L3 TOS/DSCP parameters

Connectivity

- Auto-MDIX
Provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports

Performance

- **NEW** Energy-efficient Ethernet support
Supports new IEEE 802.3az standard; and allows lower power consumption, when operated with IEEE-compliant client devices in 100 Mb/s mode only (JG708A, J9662A, and J9663A)
- Half-/full-duplex auto-negotiating capability on every port
Doubles the throughput of every port
- **NEW** Jumbo frame support
Allows frames up to 9,216 bytes to be switched through the network (Gigabit Ethernet models)
- Mini jumbo-frame support
Allows frames up to 2,048 bytes to be switched through the network, which supports large data transfers (J9662A and J9663A)

Ease of use

- Unmanaged

Provides plug-and-play simplicity

- Comprehensive LED display with per-port indicators

Provides an at-a-glance view of the status, activity, speed, and full-duplex operation of the switches

- Flow control

Helps ensure reliable communications during full-duplex operation

- Auto-speed negotiation

Selects individual port speed automatically, depending on client capabilities; removing the need for manual intervention enables simple plug-and-play operation

Flexibility

- Fan-less design

Enables quiet operation for deployment in open spaces

- **NEW** Internal power supply

Delivers operational convenience and an environment suitable for business operations (JG708A, J9561A, and JD986B)

Warranty and support

- **NEW** Lifetime Warranty 2.0

Advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)¹

- **NEW** Electronic and telephone support (for Lifetime Warranty 2.0)

Limited 24x7 telephone support is provided by HP for the first three years; limited electronic and telephone support during business hours is provided by HP for the complete warranty period; to reach our support centers, visit hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, visit hp.com/networking/warrantysummary

¹ HP warranty includes repair or replacement of hardware for as long as you own the product, with next-business-day advance replacement (available in most countries). The disk drives included—with the HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765 zL Mobility Controller, and HP Survivable Branch Communication zL Module powered by Microsoft® Lync—each have a five-year hardware warranty. For details, refer to the software license and hardware warranty statements at hp.com/networking/warranty.

HP 1410 Switch Series

Specifications



	HP 1410-8G Switch (J9559A)	HP 1410-16G Switch (J9560A)	HP 1410-24G-R Switch (JG708A)
Ports	8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 8 autosensing 10/100/1000 ports	16 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 16 autosensing 10/100/1000 ports	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 24 autosensing 10/100/1000 ports
Physical characteristics	6.14(w) x 3.8(d) x 0.96(h) in (15.6 x 9.65 x 2.45 cm)	8.21(w) x 4.41(d) x 1.73(h) in (20.85 x 11.2 x 4.4 cm) (1U height)	17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height)
Weight	0.74 lb (0.34 kg)	1.43 lb (0.65 kg)	6.61 lb (3 kg)
Memory and processor	4 Kb EEPROM capacity; packet buffer size: 192 KB	512 Kb flash; packet buffer size: 512 KB	1 MB flash; packet buffer size: 512 KB
Mounting	Wall, desktop and under-table mounting	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	Mounts in an EIA standard 19-inch telco rack (hardware included); desktop mounting
Performance			
100 Mb Latency	< 3.6 μ s (LIFO 64-byte packets)	< 8.0 μ s (LIFO 64-byte packets)	< 8.0 μ s (LIFO 64-byte packets)
1000 Mb Latency	< 1.2 μ s (LIFO 64-byte packets)	< 3.6 μ s (LIFO 64-byte packets)	< 3.6 μ s (LIFO 64-byte packets)
Throughput	up to 11.9 million pps (64-byte packets)	up to 23.8 million pps (64-byte packets)	35.7 million pps (64-byte packets)
Switching capacity	16 Gb/s	32 Gb/s	48 Gb/s
MAC address table size	4096 entries	8192 entries	8192 entries
Environment			
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing	15% to 95% @ 104°F (40°C), noncondensing	5% to 95% @ 104°F (40°C), noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	15% to 90% @ 149°F (65°C), noncondensing	15% to 90% @ 149°F (65°C), noncondensing	15% to 90% @ 149°F (65°C), noncondensing
Altitude	up to 10,000 ft (3 km)	up to 10,000 ft (3 km)	up to 16,404 ft (5 km)
Acoustic	Power: 0 dB No fan	Power: 0 dB No fan	Power: 0 dB No fan

	HP 1410-8G Switch (J9559A)	HP 1410-16G Switch (J9560A)	HP 1410-24G-R Switch (JG708A)
Electrical characteristics			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	41 BTU/hr (43.26 kJ/hr)	44 BTU/hr (46.42 kJ/hr)	55 BTU/hr (58 kJ/hr)
Voltage	100-240 VAC	100-240 VAC	100-240 VAC
Current	1.0 A	1.1 A	0.3 A
Maximum power rating	12 W	13 W	16 W
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. This model provides internal power supply. Please select the correct power cord country option.
Safety			
	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950-1	CSA 22.2 No. 60950; UL 60950-1; IEC 60950-1; EN 60950-1	CSA 22.2 No. 60950; UL 60950-1; IEC 60950-1; EN 60950-1
Emissions			
	FCC Rules Part 15, Subpart B Class A	FCC Rules Part 15, Subpart B Class A	FCC Rules Part 15, Subpart B Class A
Immunity			
Generic	EN 55022 CISPR 22	EN 55022 CISPR 22	EN 55022 CISPR 22
EN	EN 55024, CISPR 24	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11	IEC 61000-4-11
Harmonics	IEC 61000-3-2	IEC 61000-3-2	IEC 61000-3-2
Flicker	IEC 61000-3-3	IEC 61000-3-3	IEC 61000-3-3
Notes			
IEEE 802.3az Energy Efficient Ethernet protocol is supported by the HP 1410-24G-R (JG708A), HP 1410-16 (J9662A) and HP 1410-24 (J9663A) Switches.			

	HP 1410-8G Switch (J9559A)	HP 1410-16G Switch (J9560A)	HP 1410-24G-R Switch (JG708A)
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF795E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UF796E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR843E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR844E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR816E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR817E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR818E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR819E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW386E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW387E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW388E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR845E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW389E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW390E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW391E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW389E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW390E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW391E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

HP 1410 Switch Series

Specifications (continued)



	HP 1410-24G Switch (J9561A)	HP 1410-8 Switch (J9661A)	HP 1410-16 Switch (J9662A)
Ports	22 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab 1000BASE-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers) Supports a maximum of 24 Gigabit Ethernet ports	8 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full Supports a maximum of 8 autosensing 10/100 ports	16 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full Supports a maximum of 16 autosensing 10/100 ports
Physical characteristics	13.23(w) x 6.65(d) x 1.73(h) in (33.6 x 16.9 x 4.4 cm) (1U height)	6.14(w) x 3.74(d) x 0.97(h) in (15.6 x 9.5 x 2.46 cm)	8.21(w) x 4.21(d) x 1.73(h) in (20.85 x 10.69 x 4.39 cm) (1U height)
Weight	2.98 lb (1.35 kg)	0.74 lb (0.34 kg)	1.43 lb (0.65 kg)
Memory and processor	512 Kb flash; packet buffer size: 512 KB	16 Kb EEPROM; packet buffer size: 96 KB	16Kb EEPROM; packet buffer size: 2 Mb
Mounting	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	Wall, desktop and under-table mounting	Mounts in an EIA standard 19-inch telco rack (hardware included) wall, desktop and under-table mounting
Performance			
100 Mb Latency	< 8.0 μs (LIFO 64-byte packets)	< 3.7 μs (LIFO 64-byte packets)	< 10.6 μs (LIFO 64-byte packets)
1000 Mb Latency	< 3.6 μs (LIFO 64-byte packets)		
Throughput	up to 35.7 million pps (64-byte packets)	up to 1.1 million pps (64-byte packets)	up to 2.3 million pps (64-byte packets)
Switching capacity	48 Gb/s	1.6 Gb/s	3.2 Gb/s
MAC address table size	8192 entries	1024 entries	8192 entries

	HP 1410-24G Switch (J9561A)	HP 1410-8 Switch (J9661A)	HP 1410-16 Switch (J9662A)
Environment			
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing	15% to 95% @ 104°F (40°C), noncondensing	5% to 95% @ 104°F (40°C), noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	15% to 90% @ 149°F (65°C), noncondensing	15% to 90% @ 149°F (65°C), noncondensing	15% to 90% @ 149°F (65°C), noncondensing
Altitude	up to 10,000 ft (3 km)	up to 10,000 ft (3 km)	up to 16,404 ft (5 km)
Acoustic	Power: 0 dB No fan	Power: 0 dB No fan	Power: 0 dB No fan
Electrical characteristics			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	75 BTU/hr (79.13 kJ/hr)	13 BTU/hr (13.72 kJ/hr)	13 BTU/hr (13.72 kJ/hr)
Voltage	100-240 VAC	100-240 VAC	100-240 VAC
DC voltage		12 V	12 V
Current	0.3 A	0.3 A	0.3 A
Maximum power rating	22 W	3.6 W	3.6 W
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. This model provides internal power supply. Please select the correct power cord country option.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.
Safety			
	CSA 22.2 No. 60950; UL 60950-1; IEC 60950-1; EN 60950-1	UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009	UL 60950-1; CSA C22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009
Emissions			
	FCC Rules Part 15, Subpart B Class A	FCC Rules Part 15, Subpart B Class A	FCC Rules Part 15, Subpart B Class A

	HP 1410-24G Switch (J9561A)	HP 1410-8 Switch (J9661A)	HP 1410-16 Switch (J9662A)
Immunity			
Generic	EN 55022 CISPR 22	EN 55022 CISPR 22	EN 55022 CISPR 22
EN	EN 55024, CISPR 24	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11	IEC 61000-4-11
Harmonics	IEC 61000-3-2	IEC 61000-3-2	IEC 61000-3-2
Flicker	IEC 61000-3-3	IEC 61000-3-3	IEC 61000-3-3

Notes

Use only supported genuine HP mini-GBICs with your switch.

IEEE 802.3az Energy Efficient Ethernet protocol is supported by the HP 1410-24G-R (JG708A), HP 1410-16 (J9662A) and HP 1410-24 (J9663A) Switches.

Services

3-year, 4-hour onsite, 13x5 coverage for hardware (UF795E)	3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)	3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)
3-year, 4-hour onsite, 24x7 coverage for hardware (UF796E)	3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)	3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)
1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR843E)	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR844E)	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UR817E)	4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)	4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)
3-year 6 hr Call-to-Repair Onsite (UW386E)	4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)	4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)
1-year, 6 hour Call-To-Repair Onsite for hardware (HR845E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)
Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)
	3-year 6 hr Call-to-Repair Onsite (UW389E)	3-year 6 hr Call-to-Repair Onsite (UW389E)
	4-year 6 hr Call-to-Repair Onsite (UW390E)	4-year 6 hr Call-to-Repair Onsite (UW390E)
	5-year 6 hr Call-to-Repair Onsite (UW391E)	5-year 6 hr Call-to-Repair Onsite (UW391E)
	1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)	1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)
	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1410 Switch Series

Specifications (continued)



	HP 1410-24 Switch (J9663A)	HP 1410-24-R Switch (JD986B)	HP 1410-24-2G Switch (J9664A)
Ports	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 24 autosensing 10/100 ports	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 24 autosensing 10/100 ports	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 24 autosensing 10/100 ports plus 2 autosensing 10/100/1000 ports
Physical characteristics	13.23(w) x 6.65(d) x 1.73(h) in (33.6 x 16.89 x 4.39 cm) (1U height) Weight 2.98 lb (1.35 kg)	17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height) Weight 4.41 lb (2.0 kg)	13.23(w) x 6.65(d) x 1.73(h) in (33.6 x 16.89 x 4.39 cm) (1U height) Weight 2.98 lb (1.35 kg)
Memory and processor	16 Kb EEPROM; packet buffer size: 2 Mb	8kb EEPROM; packet buffer size: 2 Mb	2 Kb EEPROM; packet buffer size: 2.5 Mb
Mounting	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	Mounts in an EIA standard 19-inch telco rack (hardware included); desktop mounting	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting
Performance	100 Mb Latency < 11 μ s (LIFO 64-byte packets) 1000 Mb Latency < 11 μ s (LIFO 64-byte packets) Throughput up to 3.5 million pps (64-byte packets) Switching capacity 4.8 Gb/s MAC address table size 8192 entries	100 Mb Latency < 11 μ s (LIFO 64-byte packets) 1000 Mb Latency < 11 μ s (LIFO 64-byte packets) Throughput 3.5 million pps (64-byte packets) Switching capacity 4.8 Gb/s MAC address table size 8192 entries	100 Mb Latency < 5.6 μ s (LIFO 64-byte packets) 1000 Mb Latency < 2.2 μ s (LIFO 64-byte packets) Throughput up to 6.5 million pps (64-byte packets) Switching capacity 8.8 Gb/s MAC address table size 8192 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 90% @ 149°F (65°C), noncondensing Altitude up to 10,000 ft (3 km) Acoustic Power: 0 dB No fan	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 90% @ 149°F (65°C), noncondensing Altitude up to 10,000 ft (3 km) Acoustic Power: 0 dB No fan	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 95% @ 104°F (40°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 90% @ 149°F (65°C), noncondensing Altitude up to 16,404 ft (5 km) Acoustic Power: 0 dB No fan
Electrical characteristics	Frequency 50/60 Hz Maximum heat dissipation 17 BTU/hr (17.93 kJ/hr) Voltage 100-240 VAC DC voltage 12 V Current 0.4 A Maximum power rating 4.8 W Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.	Frequency 50/60 Hz Maximum heat dissipation 21 BTU/hr (22 kJ/hr) Voltage 100-240 VAC DC voltage 3.3 V Current 1.1 A Maximum power rating 3.6 W Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. This model provides an internal power supply. Please select the correct power cord country option.	Frequency 50/60 Hz Maximum heat dissipation 37 BTU/hr (39.03 kJ/hr) Voltage 100-240 VAC DC voltage 12 V Current 0.9 A Maximum power rating 10.8 W Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.

	HP 1410-24 Switch (J9663A)	HP 1410-24-R Switch (JD986B)	HP 1410-24-2G Switch (J9664A)
Safety	UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009	UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009	UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009
Emissions	FCC Rules Part 15, Subpart B Class A	FCC Rules Part 15, Subpart B Class A	FCC Rules Part 15, Subpart B Class A
Immunity			
Generic	EN 55022 CISPR 22	EN 55022 CISPR 22	EN 55022 CISPR 22
EN	EN 55024, CISPR 24	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11	IEC 61000-4-11
Harmonics	IEC 61000-3-2	IEC 61000-3-2	IEC 61000-3-2
Flicker	IEC 61000-3-3	IEC 61000-3-3	IEC 61000-3-3
Notes	IEEE 802.3az Energy Efficient Ethernet protocol is supported by the HP 1410-24G-R (JG708A), HP 1410-16 (J9662A) and HP 1410-24 (J9663A) Switches.		
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW389E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW390E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW391E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW389E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW390E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW391E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF797E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UF798E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR846E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR847E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR820E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR821E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR822E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR823E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW389E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW390E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW391E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR848E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
Standards and Protocols (applies to all products in series)			
General protocols	IEEE 802.1p Priority	IEEE 802.3ab 1000BASE-T Gigabit Ethernet over twisted pair (10/100/1000 models only) IEEE 802.3i 10BASE-T Ethernet over twisted pair	IEEE 802.3u 100BASE-TX Fast Ethernet, 100BASE-FX with auto negotiation IEEE 802.3x Flow Control

HP 1410 Switch Series accessories

Cables

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)
HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)
HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)
HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)
HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)
HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)
HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)

HP 1410-24G Switch (J9561A)

HP X121 1G SFP LC SX Transceiver (J4858C)
HP X121 1G SFP LC LX Transceiver (J4859C)
HP X111 100M SFP LC FX Transceiver (J9054C)

Learn more at
hp.com/networking

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2010-2011, 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of Microsoft Corporation.

4AA1-1585ENW, November 2013, Rev. 4

